




## Model RA-C (Single-Split Type)



Model RA...C



Model RA...CUU

Unit: mm

Shaft diameter	Model No.	Main dimensions							Shoulder height		Basic load rating (radial)		Mass
		Inner diameter d	Outer diameter D	Roller pitch circle diameter dp	Width B B <sub>1</sub>	Greasing hole d <sub>o</sub>	r <sub>min</sub>	ds	Dh	C	C <sub>0</sub>	kg	
50	RA 5008C	50	66	57	8	1.5	0.5	53.5	60.5	5.1	7.19	0.08	
60	RA 6008C	60	76	67	8	1.5	0.5	63.5	70.5	5.68	8.68	0.09	
70	RA 7008C	70	86	77	8	1.5	0.5	73.5	80.5	5.98	9.8	0.1	
80	RA 8008C	80	96	87	8	1.5	0.5	83.5	90.5	6.37	11.3	0.11	
90	RA 9008C	90	106	97	8	1.5	0.5	93.5	100.5	6.76	12.4	0.12	
100	RA 10008C	100	116	107	8	1.5	0.5	103.5	110.5	7.15	13.9	0.14	
110	RA 11008C	110	126	117	8	1.5	0.5	113.5	120.5	7.45	15	0.15	
120	RA 12008C	120	136	127	8	1.5	0.5	123.5	130.5	7.84	16.5	0.17	
130	RA 13008C	130	146	137	8	1.5	0.5	133.5	140.5	7.94	17.6	0.18	
140	RA 14008C	140	156	147	8	1.5	0.5	143.5	150.5	8.33	19.1	0.19	
150	RA 15008C	150	166	157	8	1.5	0.5	153.5	160.5	8.82	20.6	0.2	
160	RA 16013C	160	186	172	13	2	0.8	165	179	23.3	44.9	0.59	
170	RA 17013C	170	196	182	13	2	0.8	175	189	23.5	46.5	0.64	
180	RA 18013C	180	206	192	13	2	0.8	185	199	24.5	49.8	0.68	
190	RA 19013C	190	216	202	13	2	0.8	195	209	24.9	51.5	0.69	
200	RA 20013C	200	226	212	13	2	0.8	205	219	25.8	54.7	0.71	

Note) The model number of a type with seals attached is RA...CUU.

If a certain level of accuracy is required, this model is used for inner ring rotation.

### Model number coding

**RA6008C** | **UU** | **C0**

Model number

Radial clearance symbol (\*1)

Seal attached on both ends (seal attached on either end: U)

(\*1) See **A18-17**.