



# RecondOil Core

## A simple solution for optimal oil cleanliness.

A depth filter designed for offline oil filtration that removes both large and small contaminants down to 0.1 µm, delivering clean oil that enhances machine life and supports cost-effective maintenance.

During the filtration process, the oil flows vertically down through axial gaps between sheets of paper. This allows the filter to remove particles, both hard and soft (often oxidation byproduct residues such as insoluble varnish), and water (both free, emulsified and bound), by adsorption and absorption. Particles are adsorbed to the cellulose surface, and water is absorbed by the cellulose.

### Removes all types of contamination:

- Particles
- Oxidation degradation products and varnish
- Water (free, bound and emulsified)

### Dirt holding capacity

Water absorption	3 L
Solids	3 kg
Varnish	1.5 kg

The total dirt holding capacity will depend on every application with its specifications, oil type, temperatures, humidity etc. as well as the distribution and combination of contamination types.

### ROBX500/HY

Dry weight	2.5 kg	Max oil temperature (peak)	110 °C
Operating weight	2.5-7.5 kg	Max oil temperature (steady)	130 °C
Depth	196 mm	Running mode (recommended)	Set pressure 3.5 bar
Width	196 mm	Packing	1 and 4 pcs
Height	255 mm	Material	Cellulose, Polypropylene Homopolymer

© SKF and RECONDOIL are registered trademarks of AB SKF (publ).  
 © SKF Group 2025. All rights reserved. Please note that this publication may not be copied or distributed, in whole or in part, unless prior written permission is granted.  
 Every care has been taken to ensure the accuracy of the information contained in this publication, but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.  
 PUB LS/S6 19421/1 EN · Dec 2025  
 Certain image(s) used under license from shutterstock.com