


Lever grease Pompe gresare cu guns

Hand lever grease guns are designed for lubrication of bearings, or other types of lubrication points, through grease nipples and also for free application.

We offer a wide range of these grease guns, with different reservoir volumes and accessories, in basic, standard or de luxe designs. All bellow mentioned grease guns have M10x1 outlet thread for connection of lubrication extension. Hose or tube lubrication extension is necessary to order separately - see accessorie below.

Possibilities of filling of reservoir

- a) suction from bucket with grease or other way of free filling
- b) standard cartridge 400 g according to DIN 1284
- c) filling with filler pump through filler valve according to DIN 1283



Accessories

Description of Accessories	Order No.	Picture
Hose extension, length 500 mm with hydraulic coupler (for grease nipples H)	39221	
Hose extension, length 500 mm with button-head coupler d10 mm (M4)	39239	Date
Hose extension, length 500 mm with button-head coupler d16 mm (M1, T1, T1/B)	39239	0.00
Hose extension, length 500 mm with button-head coupler d22 mm (M22)	39243	0
Tube extension, length 150 mm with hydraulic coupler (H)	39255	
Tube extension, length 150 mm with pointed nozzle (D)	39257	23

Other accessories (couplers, quick couplers etc.) is available upon request.



Type ECO-LUBE



Type 75/PK



Type ULTRA 75/PKU



Type 75/PKM



Type 75/LL

Lever grease guns

Type design	Order number	Reservoir volume [cm³]	Included accessories		ssibility filling b c	[cm³/stroko]	Max. pressure [bar]	Outlet thread		
ECO-LUBE basic	31221	450	filler valve	Х	x x	1,4	600	M10x1		
75/PK standard	31226	450	air release valve	Χ	X	1,9	800	M10x1		
ULTRA 75/PKU de luxe	31233	450	filler valve	Χ	x x	1,9	800	M10x1		
75/PKM standard	31237	450	air release valve, pressure gauge 1000 bar	Χ	X	1,9	800	M10x1		
75/LL standard	31241	1000	air release valve	X	X*	1,9	800	M10x1		

Tel.: +40 257 211 119

Fax: +40 257 211 021

e-mail: gresare@hennlich.ro

^{*} Is possible, but in the face of the reservoir volume it is inconvenient. Upon request are these grease guns available also with thread G1/8".